

Category	Picture	Description	Price
2		<p><b>P/N: POT-200B-LC Solder Pot</b>  <b>Q'ty: 1 unit</b></p> <ul style="list-style-type: none"> <li>It can be used for various electronic and electrical manufacturing especially useful when tinning small components or the ends of stripped wires.</li> <li>Power rating is 200W with a range from 180-430 °C (356-806 °F)</li> <li>Solder bath dimensions: 70x48 mm (2.76" x 1.89")</li> <li>Solder bath depth: 50 mm (1.99")</li> </ul>	<b>\$ 250.00</b>
2		<p><b>P/N: POT-400B-LC Solder Pot</b>  <b>Q'ty: 2 units</b></p> <ul style="list-style-type: none"> <li>It can be used for various electronic and electrical manufacturing especially useful when tinning small components or the ends of stripped wires.</li> <li>Power rating is 200W with a range from 180-430 °C (356-806 °F)</li> <li>Solder bath dimensions: 100x70 mm (3.94" x 2.76")</li> <li>Solder bath depth: 50 mm (1.99")</li> </ul>	<b>\$ 289.00</b>
2		<p><b>P/N: SE-26012 Spool Solder</b>  <b>Q'ty: 1 pc</b></p> <ul style="list-style-type: none"> <li>Spool rosin core</li> <li>Diameter: 0.050" (1.2 mm)</li> <li>Melting point: 183-190 °C (361-374 °F)</li> <li>Sn/Pb: 50/50 200g (~1/2 lb)</li> </ul>	<b>\$ 6.90</b>
2		<p><b>P/N: SE-26008RMA RMA Wash Free Solder</b>  <b>Q'ty: 6 pcs</b></p> <ul style="list-style-type: none"> <li>The RMA series is high capacity solder containing rosin and developed to be wash free.</li> <li>Diameter: 0.032" (0.8 mm)</li> <li>Melting point: 183-190 °C (361-374 °F)</li> <li>Sn/Pb: 60/40 200g (~1/2 lb)</li> </ul>	<b>\$ 7.90</b>
2		<p><b>P/N: SE-26010RMA RMA Wash Free Solder</b>  <b>Q'ty: 15 pcs</b></p> <ul style="list-style-type: none"> <li>The RMA series is high capacity solder containing rosin and developed to be wash free.</li> <li>Diameter: 0.040" (1.0 mm)</li> <li>Melting point: 183-190 °C (361-374 °F)</li> <li>Sn/Pb: 60/40 200g (~1/2 lb)</li> </ul>	<b>\$ 7.90</b>