

Category	Picture	Description	Price
2		<p><b>P/N: SE-26008PL                      Power Solder</b></p> <p>Q'ty: 6 pcs</p> <ul style="list-style-type: none"> <li>Compared with Eutectic solder, the rate of solder crack during thermal cycle tests is less than 1/8.</li> <li>The highest quality materials used to minimize smell.</li> <li>Diameter: 0.032" (0.8 mm)</li> <li>Sn/Pb 63/37 200g (~1/2 lb)</li> <li>Melting point: 179-189°C ( 354-372°F)</li> </ul>	<b>\$ 8.90</b>
2		<p><b>P/N: SE-26010PL                      Power Solder</b></p> <p>Q'ty: 1 pc</p> <ul style="list-style-type: none"> <li>Compared with Eutectic solder, the rate of solder crack during thermal cycle tests is less than 1/8.</li> <li>The highest quality materials used to minimize smell.</li> <li>Sn/Pb 63/37 200g (~1/2 lb)</li> <li>Diameter: 0.040" (1.0 mm)</li> <li>Melting point: 179-189°C ( 354-372°F)</li> </ul>	<b>\$ 8.90</b>
2		<p><b>P/N: SE-26012PL                      Power Solder</b></p> <p>Q'ty: 1 pc</p> <ul style="list-style-type: none"> <li>Compared with Eutectic solder, the rate of solder crack during thermal cycle tests is less than 1/8.</li> <li>The highest quality materials are used to minimize smell.</li> <li>Sn/Pb 63/37 200g (~1/2 lb)</li> <li>Diameter: 0.050" (1.2 mm)</li> <li>Melting point: 179-189°C ( 354-372°F)</li> </ul>	<b>\$ 8.90</b>
2		<p><b>P/N: 6S-6                      Soldering Iron Stand</b></p> <p>Q'ty: 1 pc</p> <ul style="list-style-type: none"> <li>Holds up to 1 1/8" diameter iron</li> <li>Sponge receptacle</li> <li>Heavy duty metal base</li> </ul>	<b>\$ 3.90</b>